

FIREMAN'S OUTFIT



HXXF-46A EXTINGUISHER BOX
 Size: 755mm*305mm*225mm
 Material: FRP



HJF-47 STAND BOX
 size: 500mm*300mm*300mm
 Material: FRP



HJF-47T STAND BOX
 size: 460mm*300mm*300mm
 Material: Stainless steel



MT/5 CO₂ FIRE EXTINGUISHER 5kg
 Diameter: 155mm
 Maximum working pressure: 17Mpa
 Test pressure: 25Mpa
 Minimum wall thickness: $\geq 3.0\text{mm}$
 Material: Steel
 Fire Rating: 34B
 Standard: CCS / ZY / EC



MT/7 CO₂ FIRE EXTINGUISHER 7kg
 Diameter: 155mm
 Maximum working pressure: 17Mpa
 Test pressure: 25Mpa
 Minimum wall thickness: $\geq 3.4\text{mm}$
 Material: Alloy Steel
 Fire Rating: 55B
 Standard: CCS / ZY / EC



MFZ/ABC 5kg POWDER FIRE EXTINGUISHER
 Diameter: 150mm
 Maximum working pressure: 1.2Mpa
 Ambient temperature: $-20^{\circ}\text{C} \sim +55^{\circ}\text{C}$
 Test pressure: 2.1Mpa
 Minimum wall thickness: $\geq 1.3\text{mm}$
 Material: Carbon Steel
 Fire Rating: 3A89B
 Standard: CCS / ZY / EC

**MFZ/ABC 6kg POWDER FIRE EXTINGUISHER**

Diameter: 150mm
Maximum working pressure: 1.2Mpa
Ambient temperature: -20°C~+55°C
Test pressure: 2.1Mpa
Minimum wall thickness: $\geq 1.3\text{mm}$
Material: Carbon Steel
Fire Rating: 3A89B
Standard: CCS / ZY / EC

**MFZ/ABC 35kg WHEELED POWDER FIRE EXTINGUISHER**

Diameter: 325mm
Maximum working pressure: 1.2Mpa
Ambient temperature: -20°C~+55°C
Test pressure: 2.1Mpa
Minimum wall thickness: $\geq 3.8\text{mm}$
Material: Carbon Steel
Fire Rating: 6A183B
Standard: CCS / ZY / EC

**MFZ/ABC 8kg POWDER FIRE EXTINGUISHER**

Diameter: 164mm
Maximum working pressure: 1.2Mpa
Ambient temperature: -20°C~+55°C
Test pressure: 2.1Mpa
Minimum wall thickness: $\geq 2.5\text{mm}$
Material: Carbon Steel
Fire Rating: 4A144B
Standard: CCS / ZY / EC