

FIREMAN'S OUTFIT



MFZ/ABC 50kg WHEELED POWDER FIRE EXTINGUISHER

Diameter: 406mm
Maximum working pressure: 1.2Mpa
Ambient temperature: -20°C ~ +55°C
Test pressure: 2.1Mpa
Minimum wall thickness: $\geq 1.3\text{mm}$
Material: Carbon Steel
Fire Rating: 10A233B
Standard: CCS / ZY / EC



MSZ/6 6L FOAM EXTINGUISHER

Diameter: 150mm
Maximum working pressure: 2.1Mpa
Ambient temperature: 5°C ~ +55°C
Test pressure: 2.1Mpa
Minimum wall thickness: $\geq 1.4\text{mm}$
Material: Carbon Steel
Fire Rating: 1A55B
Standard: CCS / ZY / EC



MSZ/9 9L FOAM EXTINGUISHER

Diameter: 180mm
Maximum working pressure: 1.2Mpa
Ambient temperature: 5°C ~ +55°C
Test pressure: 2.1Mpa
Minimum wall thickness: $\geq 2.5\text{mm}$
Material: Carbon Steel
Fire Rating: 2A89B
Standard: CCS / ZY / EC

**MSZ/45 45L WHEELED FOAM
EXTINGUISHER****Diameter:** 325mm**Maximum working pressure:** 1.2Mpa**Ambient temperature:** 5°C~+55°C**Test pressure:** 2.1Mpa**Minimum wall thickness:** ≥2.8mm**Material:** Carbon Steel**Fire Rating:** 4A183B**Standard:** CCS / ZY / EC**MSZ/65 65L WHEELED FOAM
EXTINGUISHER****Diameter:** 406mm**Maximum working pressure:** 1.2Mpa**Ambient temperature:** 5°C~+55°C**Test pressure:** 2.1Mpa**Minimum wall thickness:** ≥2.8mm**Material:** Carbon Steel**Fire Rating:** 6A233B**Standard:** CCS / ZY / EC

FIREMAN'S OUTFIT



MSZ/135 135L WHEELED FOAM EXTINGUISHER

- Diameter:** 406mm
- Maximum working pressure:** 1.2Mpa
- Ambient temperature:** 5°C~+55°C
- Test pressure:** 2.1Mpa
- Minimum wall thickness:** ≥2.8mm
- Material:** Carbon Steel
- Fire Rating:** 10A297B
- Standard:** CCS / ZY / EC



HXXXF-42 5kg/6kg FIRE EXTINGUISHER BRACKET

Type	Material	Surface treatment
HXXXF-42	Steel	spray powder
HXXXF-42A	Stainless Steel	
HXXXF-42L	Aluminum	



HXXXF-43 9L FIRE EXTINGUISHER BRACKET

Type	Material	Surface treatment
HXXXF-43	Steel	spray powder
HXXXF-43A	Stainless Steel	
HXXXF-43L	Aluminum	